



# Leica AP20 AutoPole

## Data sheet



### PoleHeight

Save time and eliminate mistakes that result from both height reading and manual input into the application software. Whenever the pole height changes, the automatic PoleHeight function will update the height settings to ensure reliable and accurate measurements.



### Tilt Compensation

Increase productivity and efficiency with tilt compensation that eliminates the necessity to level the pole. Measure inaccessible points, conveniently increase your overall measurement output and ensure highest job standards by verified compensation of the tilted pole alignment.



### TargetID

Be unstoppable with the TargetID feature! Automatic target search, identification and locking prevents measurements to foreign targets and avoids interruptions that can occur on a busy, multi-crew construction or measurement site.

leica-geosystems.com



- when it has to be **right**

**Leica**  
Geosystems

PART OF  
**HEXAGON**

# Leica AP20 AutoPole

Leica AP20 AutoPole is the only smart system on the market that solves three common workflow problems surveying and construction professionals face daily:

- entering the pole height manually into the field software
- having to level the pole
- accidentally locking to a foreign target at a busy site

The AP20 helps users work more efficiently, trust the data they gather and increase productivity overall. The result is faster completion of projects while maintaining high quality standards.



## POLEHEIGHT

Accuracy in height	At snap-lock position	+/- 1.0 mm
--------------------	-----------------------	------------

## TILT COMPENSATION

	Target height (m)	Additional 2D uncertainty for tilt down to 90°
	0.228*	typically 1 mm + 0.1 mm/° tilt
	1.600	typically 3 mm + 0.6 mm/° tilt
	2.000	typically 4 mm + 0.7 mm/° tilt
Tilt range <sup>2</sup>	+/- 180°	
Range to total station <sup>3</sup>	Typically 300 m	

## TARGETID

Number of different IDs	16
Working range	Typically 150 m

## GENERAL

Power management	Exchangeable Lithium-Ion battery (GEB321)	Operating time up to 16 h for AP20 H / AP20 ID and 6 h for AP20 T / AP20
Weight	AP20 including battery	0.5 kg (1.1 lbs)
Power management	Working temperature range Storage temperature range Dust & Water (IEC 60529) / Humidity	-30°C to +60°C (-22°F to 140°F) -40°C to +80°C (-40°F to 176°F) IP67 / 95%, non-condensing

LEICA AP20 AUTOPOLE VARIANTS	AP20 H	AP20 ID	AP20 T	AP20
PoleHeight	✓	✗	✓	✓
Tilt Compensation <sup>4</sup>	✗	✗	✓	✓
TargetID <sup>5</sup>	✗	✓	✗	✓
LEICA AP REFLECTOR POLE VARIANTS	GLS51 <sup>6</sup>	GLS51 F <sup>7</sup>	CRP4 <sup>6</sup>	CRP5 <sup>7</sup>
Surveying, stub interface	✓	✓	✗	✗
Construction, 5/8" screw interface	✗	✗	✓	✓
Snap lock position every	5 cm	0.2 ft	5 cm	1.0 ft

✓ = Standard ✗ = Not available

1. Measurement precision, accuracy, reliability and time for initialization are dependent upon various factors including angular and distance accuracy of the total station, target type, atmospheric conditions, target height and level of pole tilt.
2. Free line of sight to target required

\* 0.228 m refers to height with CRP10 attached to GRZ122

3. Using radio handle RH18 or CCD18, connected to CS20 with internal LR-BT
4. Requires total station with target lock functionality and radio handle RH18 or CCD18
5. Requires total station with PowerSearch functionality
6. Metric scale
7. Feet scale

The Bluetooth® trademarks are owned by Bluetooth SIG. Other trademarks and trade names are those of their respective owners.  
Copyright Leica Geosystems AG, 9435 Heerbrugg, Switzerland. All rights reserved. Printed in Switzerland – 2022.  
Leica Geosystems AG is part of Hexagon AB. 953389enus - 03.22

**Leica Geosystems AG**  
Heinrich-Wild-Strasse  
9435 Heerbrugg, Switzerland  
+41 71 727 31 31

- when it has to be **right**

**Leica**  
Geosystems